



"Easyflex" Level Mounts for Vibration/Shock/Noise Isolation

Here's All You Have To Do

- Move machine into place.
- Raise Machine
- Attach Mounts and lower machine.
Adjust leveling screws until machine is level.



"Easyflex" Mounts Take only a Few Minutes to Install.

Economy & Advantages

- "Easy Flex" Level-Mounts require no expense for floor preparation, bolts, anchor plates, masonry Drilling and re-cementing.
- Built-in levelling adjustment saves time, labour and money.
- Mounts are practically indestructible and match the life of mounted machine.
- No Foundation * Flexible Production Lines * Shock & Vibration Isolation * Reduced Maintenance & Less Noise
- Available in Oil Resistant Nitrile Rubber.

Size	Load Capacity lbs	Standard Bolt Size	Length inch/mm
Type : SC - 12	(Heavy Duty)		
EFLM-090/SC-12	1980 - 2970	1/2"/M 12	4"/100mm
EFLM-110/SC-12	2970 - 4400	5/8"/M 16	5"/125mm
EFLM-128/SC-12	3960 - 5940	5/8"/M 16	5"/125mm
EFLM-156/SC-12	5940 - 8910	3/4"/M 20	6"/150mm
EFLM-180/SC-12	7920 - 11880	3/4"/M 20	6"/150mm
EFLM-210/SC-12	10780 - 16060	1"/M 24	8"/200mm
EFLM-240/SC-12	14080 - 21120	1"/M 24	8"/200mm
EFLM-300/SC-12	22000 - 33000	As per requirement	
EFLM-400/SC-12	38720 - 58740	As per requirement	

Note : To be used with Load Factor