



Application

Designed for suspending stationary level adjustment lines.
Design of hanger allows for vertical adjustment.

Standard Material

Carbon Steel - Electro galvanized post manufacture


Other Options

- EPDM Lined (Suffix 'RL')
- Epoxy Powder Coated finish (Suffix 'PC')
- Hot Dip Galvanised finish (Suffix 'HDG')
- Stainless Steel construction (Suffix 'SS')



Ordering

Specify pipe size standard model and suffix.



Compliance - US Standards MSS-SP58 (Type 1), MSS-SP69; EG to ASTM B633 SC3, BS1706 FE/ZN12

Model No.	Pipe Size (Inches)	Safe Working Load (lbs)	Dimension (inch)			
			Upper Steel (width)	Lower Steel (width)	Hole Size	D
EFCH022-SD	1/2"	397	0.75	0.75	0.43	0.87
EFCH028-SD	3/4"	441	0.75	0.75	0.43	1.10
EFCH035-SD	1"	485	0.75	0.75	0.43	1.38
EFCH040-SD	1-1/4"	507	0.75	0.75	0.43	1.65
EFCH048-SD	1-1/2"	529	0.75	0.75	0.43	1.89
EFCH060-SD	2"	551	0.75	0.75	0.43	2.36
EFCH075-SD	2-1/2"	595	0.98	0.98	0.55	2.87
EFCH090-SD	3"	772	0.98	0.98	0.55	3.50
EFCH105-SD	3-1/2"	816	0.98	0.98	0.55	4.13
EFCH115-SD	4"	904	0.98	0.98	0.55	4.53
EFCH140-SD	5"	948	1.18	1.18	0.55	5.51
EFCH168-SD	6"	1058	1.18	1.18	0.55	6.61
EFCH219-SD	8"	1058	1.57	1.57	0.55	8.62
EFCH273-SD	10"	1257	1.57	1.57	0.67	10.75
EFCH323-SD	12"	1610	1.57	1.57	0.67	12.72

- Due to policy of continual improvement, the specifications are subject to change without prior notice.
- Measurements are subject to 5% tolerance.
- To achieve good sound suppression do not over load fitting.