



Function:

Used for fast fixing main pipe, used for single pipe transverse or longitudinal seismic, suitable for pipe arbitrary Angle connection, fixed connection slot parts can be cast.

Material:

Carbon Steel

Finish:

Electro-galvanized

Approvals:

Underwriters' Laboratories Listed in the U.S. (UL), Canada (CUL), for use with standard steel pipe sizes 1" to 8".

Ordering:

Specify Size

Item	Size (inches)	D (inch)	Support Pipe	Assembly longitudinal and transverse loads					
				Minimum Load (lbs)	Minimum Load (kg)	Minimum Load (N)	Maximum Load (lbs)	Maximum Load (kg)	Maximum Load (N)
GJZC	2"	2.40"	1" Pipe	680	306	3020	1494	673	6650
GJZC	2-1/2"	2.99"	1" Pipe	680	306	3020	1494	673	6650
GJZC	3"	3.54"	1" Pipe	680	306	3020	1494	673	6650
GJZC	4"	4.53"	1" Pipe	680	306	3020	1494	673	6650
GJZC	5"	5.55"	1" Pipe	1370	617	6090	3014	1356	13400
GJZC	6"	6.61"	1" Pipe	1370	617	6090	3014	1356	13400
GJZC	8"	8.66"	1" Pipe	1370	617	6090	3014	1356	13400