



EasyflexTM



SECTION A-A




*All dimensions are in mm.
unless specified.

Design Code:	EJMA 10th Edition			
Size:(DN)	125 NB	5 "		
Design Pressure :	10.34 bar(g)	150 PSI(g)		
Design Temperature :	250°C	482°F		
Test Pressure:	15.51 bar(g)	225 PSI(g)		
Life Cycle:	Above 10,000			
Weight:	~ 15 Kg	~ 33.07 lb		
Movement Capacity:	(+) (mm)		(-) (mm)	
	(mm)	(Inch)	(mm)	(Inch)
Axial Movement:	10	0.40"	10	0.40"
Lateral Movement:	2	0.08"	2	0.08"
Angular Movement:	0°	0°	0°	0°
Torsional Movement:	0°	0°	0°	0°

Space for Client Approval

Seal & Signature



Shipping Bar Arrangement

Notes :

1. Bellow Tolerance will be as per EJMA 10th Edition.
2. Shipping bar will be provided painted in yellow, removed it after installation.
3. All surface will be smooth finish, free from welding burrs and Sharp edges.

Testing :

1. 100% Die penetration test on weld joints where ever applicabale.
2. Raw material check test for chemical composition and mechanical properties.
3. Dimension and visual check.

3	Flange (ANSI B16.5 #150 SORF)	SS 304	2
2	Collar	A 240 Gr. 304	2
1	Bellow	A 240 Gr. 304	1
Sl.No.	Description	Material	Pcs

Bill of Material

Client Name:-

DRAWN BY	-
CHECKED BY	-
APPROVED BY	-
SCALE: NTS	
DRAWING No.	-
DATE	REV:- 00

OWNER :
Easyflex /VibraSystems

No	Revision Description	Date
----	----------------------	------