




Confidential : All rights reserved ISO 16016. No part of this document may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, without prior permission. All rights reserved in the event of the granting of a patent or the registration of a utility model or design. Offenders will be held liable for the payment of damages.



Design Code:	FSA USA Standard			
Size:(DN)	500		20 "	
Pressure Rating :	16 bar(g)		232 PSI(g)	
Max. Temperature :	115°C		239°F	
Test Pressure:	24 bar(g)		348 PSI(g)	
Movement Capacity:	(+)		(-)	
	(mm)	(Inch)	(mm)	(Inch)
Axial Movement:	28.6	1.125"	39.7	1.56"
Lateral Movement:	28.6	1.125"	28.6	1.125"
Angular Movement:	20°	20°	20°	20°



Sl.No.	Description	Material	Pcs
6	Nut , Washer	IS 1367 Cl 4.0,IS 2016 (Zinc Electroplated)	50
5	Limit Rod	IS 1367 Cl 4.6 (Zinc Electroplated)	5
4	Lugs	IS 2062 Gr.B (Hot Dip Galvanized)	10
3	Flange	IS 2062 Gr.B (Hot Dip Galvanized)	2
2	Ring	SS 304	1
1	Bellow	EPDM	1

Bill of Material

Title:-EPDM Twin Sphere Floating Flange Rubber Expansion Joint with Floating Flanges			
Client Name:-			
DRAWN BY		OWNER : Easyflex / VibraSystems	
CHECKED BY			
APPROVED BY			
SCALE: NTS			
DRAWING No.			
DATE		REV:- 00	

Notes :

- Bellow Tolerance will be as per FSA USA Standard.
- Flange drill dimension will be as per ANSI B16.5#150.
- Matching flange should be of flat face .

Testing :

- Raw material check test for chemical composition and mechanical properties.
- Dimension and visual check.

Seal & Signature		
No	Revision Description	Date