




Confidential : All rights reserved ISO 16016. No part of this document may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, without prior permission. All rights reserved in the event of the granting of a patent or the registration of a utility model or design. Offenders will be held liable for the payment of damages.



|                    |                  |        |            |        |
|--------------------|------------------|--------|------------|--------|
| Design Code:       | FSA USA Standard |        |            |        |
| Size:(DN)          | 350              |        | 14 "       |        |
| Pressure Rating :  | 20 bar(g)        |        | 290 PSI(g) |        |
| Max. Temperature : | 115°C            |        | 239°F      |        |
| Test Pressure:     | 30 bar(g)        |        | 435 PSI(g) |        |
|                    |                  |        |            |        |
| Movement Capacity: | (+)              |        | (-)        |        |
|                    | (mm)             | (Inch) | (mm)       | (Inch) |
| Axial Movement:    | 28.6             | 1.125" | 39.6       | 1.56"  |
| Lateral Movement:  | 28.6             | 1.125" | 28.6       | 1.125" |
| Angular Movement:  | 20°              | 20°    | 20°        | 20°    |



|    |                             |
|----|-----------------------------|
| A. | Inner Cover EPDM            |
| B. | Outer Cover EPDM            |
| C. | Reinforce nylon cord fabric |
| D. | Hard steel wire             |

|        |             |          |     |
|--------|-------------|----------|-----|
| 3      | Flange      | SS 304   | 2   |
| 2      | Ring        | SS 304   | 1   |
| 1      | Bellow      | EPDM     | 1   |
| Sl.No. | Description | Material | Pcs |

Bill of Material

|                                                                                            |  |                                    |  |
|--------------------------------------------------------------------------------------------|--|------------------------------------|--|
| Title:-EPDM Twin Sphere Floating Flange Rubber Expansion Joint with SS304 Floating Flanges |  |                                    |  |
| Client Name:-                                                                              |  |                                    |  |
| DRAWN BY                                                                                   |  | OWNER :<br>Easyflex / VibraSystems |  |
| CHECKED BY                                                                                 |  |                                    |  |
| APPROVED BY                                                                                |  |                                    |  |
| SCALE: NTS                                                                                 |  |                                    |  |
| DRAWING No.                                                                                |  |                                    |  |
| DATE                                                                                       |  | REV:- 00                           |  |

Notes :  
1. Bellow Tolerance will be as per FSA USA Standard.  
2. Flange drill dimension will be as per ANSI B16.5#150.  
3. Matching flange should be of flat face .  
Testing :  
1. Raw material check test for chemical composition and mechanical properties.  
2. Dimension and visual check.

|                  |                      |      |
|------------------|----------------------|------|
| Seal & Signature |                      |      |
| No               | Revision Description | Date |
|                  |                      |      |
|                  |                      |      |