




Confidential : All rights reserved ISO 16016. No part of this document may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, without prior permission. All rights reserved in the event of the granting of a patent or the registration of a utility model or design. Offenders will be held liable for the payment of damages.



A.	Inner Cover EPDM
B.	Outer Cover EPDM
C.	Reinforce nylon cord fabric
D.	Hard steel wire

Design Code:	FSA USA Standard			
Size:(DN)	350	14 "		
Pressure Rating :	20 bar(g)	290 PSI(g)		
Max. Temperature :	115°C	239°F		
Test Pressure:	30 bar(g)	435 PSI(g)		

Movement Capacity:	(+)		(-)	
	(mm)	(Inch)	(mm)	(Inch)
Axial Movement:	15	0.59"	16	0.63"
Lateral Movement:	16	0.63"	16	0.63"
Angular Movement:	15°	15°	15°	15°

Seal & Signature

5	Nut , Washer	IS 1367 Cl 4.0,IS 2016 (Zinc Electroplated)	40
4	Limit Rod	IS 1367 Cl 4.6 (Zinc Electroplated)	4
3	Lugs	IS 2062 Gr.B (Hot Dip Galvanized)	8
2	Flange	IS 2062 Gr.B (Hot Dip Galvanized)	2
1	Bellow	EPDM	1
Sl.No.	Description	Material	Pcs

Bill of Material

Title:-EPDM Floating Flange Rubber Expansion Joint with Floating Flanges

Client Name:-

DRAWN BY
CHECKED BY
APPROVED BY

OWNER :
Easyflex / VibraSystems

SCALE: NTS

DRAWING No.

DATE

REV:- 00

- Notes :
1. Bellow Tolerance will be as per FSA USA Standard.
 2. Flange drill dimension will be as per ANSI B16.5#150.
 3. Matching flange should be of flat face .
- Testing :
1. Raw material check test for chemical composition and mechanical properties.
 2. Dimension and visual check.

No	Revision Description	Date
----	----------------------	------