




SECTION A-A

*All dimensions are in mm. unless specified.

Size:(DN)	200 NB	8"
Design Pressure :	13 bar(g)	188.5 PSI(g)
Design Temperature :	23°C	73.4°F
Test Pressure:	19 bar(g)	275.5 PSI(g)
Minimum Centerline Bend Radius		
Static:	500 mm	20"
Dynamic:	1015 mm	40"

Notes :

1. All surface will be smooth finish, free from welding burrs and Sharp edges.
2. The Burst pressure is 4 times the Design Pressure.

Testing :

1. 100% Die penetration test on weld joints where ever applicabale.
2. Raw material check test for chemical composition and mechanical properties.
3. Dimension and visual check.

Space for Client Approval

Seal & Signature

4	Flange (ANSI B16.5 #150 SORF)	SS 304	2
3	Double Braiding	SS 304	1
2	Neck ring	SS 304	2
1	Corrugation	A 240 Gr. 304	1
Sl.No.	Description	Material	Pcs

Bill of Material

Title:- Flexible Metallic Pump Connector with Both Side Fixed Flange

DRAWN BY :
CHECKED BY :
APPROVED BY :

SCALE: NTS

DRAWING No. -

DATE

REV:- 00

OWNER :
Easyflex /VibraSystems

No	Revision Description	Date
----	----------------------	------